

# KONICA MINOLTA 363

## Configuration Page

### Print Operation Menu Map

**Basic Setting**  
Default Paper Size = A4  
Paper Tray = Auto  
Output Tray = Elevate Tray  
Binding Position = Left Binding  
Double-Sided = Off  
Staple = Off  
Hole-Punch = Off  
Orientation = Portrait  
# of Sets = 1  
No Matching Paper in Tray Setting = Stop Printing (Tray Fixed)  
Spool Setting = Off  
Convert = Off  
PDL Setting = Auto  
Banner Setting = Disable  
Banner Paper Tray = Auto

**PCL Setting**  
Font Source = 1  
Font Number = 0  
Font Point = 12.00  
Font Pitch = 10.00  
Symbol Set = PC-8, Code Page 437  
Line/Page = 64 [Line / Page]  
CRLF Mapping = Off

**PS Setting**  
Print Reports = Disable  
Text RGB Source = 4  
Text Destination Profile = Auto  
Image RGB Source = 4  
Image Destination Profile = Auto  
Graphics RGB Source = 4  
Graphics Destination Profile = Auto  
Simulation Profile = None

**XPS Settings**  
Verify XPS Digital Signature = Disable

**Test Print**  
Configuration  
PCL Font List  
PS Font List  
Demo Page

**I/F Setting**  
Network Rx Timeout = 60 [sec.]  
USB Timeout = 60 [sec.]  
Print XPS Errors = Enable

### Installed

Printer HDD = None  
Printer Memory = 2304 [MByte]

### Printer Information

**Installed Tray**  
Tray 1 = A4  
Tray 2 = A4  
Tray 3 = A4  
Tray 4 = A4  
LCI = A4

### Option

Duplex Unit = Installed  
Finisher = Not Available  
Punch Unit = Not Available  
Fold Unit = Not Available  
Fax Unit = Available  
Mailbin Unit = Not Available

### Firmware Version

Management Version = 3  
Printer Controller = A1UD0Y0-3000-G00-67

### Network

**MAC Address**  
MAC Address = 00:20:6B:7A:D6:D2

### TCP/IP

TCP/IP = Enable  
IP Address = 192.168.0.144  
Subnet Mask = 255.255.255.0  
Default Gateway = 192.168.0.1  
RAW Port 0 = 9100  
RAW Port 1 = 9112  
RAW Port 2 = 9113  
RAW Port 3 = 9114  
RAW Port 4 = 9115  
RAW Port 5 = 9116

### Network

Network = Disable

### Appletalk

Appletalk = Disable

### SMB

SMB = Enable

FASD

DAS

JPSE

SFJTKDSDVKTSV